

# NEFAB RePak P

A proven flexible, lightweight pallet collar system. This cost-effective reusable packaging concept provides high volume utilization and ergonomical handling.

All NEFAB products meet international regulations (ISPM #15) which ensures our wood packaging is safe for export.



SE-yyxxxx  
HT KD DB



NEFAB's RePak P pallet collar system has been used successfully for over 40 years. Our satisfied customers include those in the telecom and vehicles industries, as well as wholesale distributors. It is also perfectly suited for use in returnable packaging pools. The size of the packaging can be varied by increasing or decreasing the number of collars used, facilitating an optimized unit load.

For example, the combination of three pallet collar heights: 8", 12", and 16" enables unit load heights from 8" up to 44" in increments of 4".

Nefab's characteristic combination of sheet material with steel components offers an exceptional collapsibility ratio for return transport. It also allows a high degree of design flexibility. The pallet collars can be easily customized by length and width, and present optional features such as hand holes, drop down gates, and various forms of surface treatment.

The RePak system exhibits outstanding durability. The packaging lasts for a long time, protecting your goods under the toughest conditions. A reported lifetime of more than 100 transport cycles is not unusual under normal operating conditions.





# SPECIFICATIONS NEFAB REPAK P

## Material Specifications

Sheet material specification	Spruce plywood, WBP CP/C grade
Steel specification	Galvanized, euronorm DX51D+Z200
Sheet material thickness, collar	1/2"
Steel material thickness	1/16"
Height, folded collar	3.5"

## Options

Lid	Plywood with wooden battens or steel corners
Marking	Printing, Label holders
Recommended min size (external)	32.0 x 24.0 x 8.0"
Recommended max size (external)	95.0 x 48.0 x 48.0"
Other	Hinged gates, grip holes, vertical dividers

## Technical Performance

Max stacking load (static)	13,400 lbs
Max net weight of goods	600 - 1,600 lbs
Functional temperature	-40°F to 176°F
Mechanical strength test report	MVEE A 383

## Box Specifications: 48" x 40"

(all specifications include stringer pallet)	(ex: 2 x 12" 6-hinge collars, pallet and lid)
External dimension, erected box	48" x 40" x 30"
Internal dimension, erected box	47" x 39" x 24"
External dimension, collapsed box	48" x 24" x 9"
External volume, erected box	33.3 cubic ft
Internal volume, erected box	25.5 cubic ft
Volume efficiency (internal/external)	76%
Return ratio (collapsed/erected)	3:1
Tare weight per collar	22 lbs