



## ShockWatch® 2 Indicadores de Impacto

El peso y tamaño del embalaje son los dos elementos clave a tener en consideración a la hora de seleccionar un indicador de impacto ShockWatch 2. Para la selección del indicador se debe tener en cuenta también la fragilidad del producto.

### GUIDE AND TECHNICAL INFORMATION

ShockWatch2	5 - 15 ft³ .14 - .42 m³	15 - 50 ft³ .42 - 1.42 m³	50 - 100 ft³ 1.42 - 2.83 m³	100 - 250 ft³ 2.83 - 7.08 m³	250 - 500 ft³ 7.08 - 14.16 m³	500 - 1,000 ft³ 14.16 - 304.8 m³	1,000+ ft³ 304.8+ m³
0 - 10 lbs 0 - 5 kg	75G	75G	50G	37G	N/A	N/A	N/A
10 - 25 lbs 5 - 11 kg	75G	50G	50G	37G	25G	N/A	N/A
25 - 50 lbs 11 - 23 kg	50G	50G	37G	25G	25G	15G	N/A
50 - 100 lbs 23 - 45 kg	50G	37G	37G	25G	15G	15G	10G
100 - 250 lbs 45 - 113 kg	37G	37G	25G	25G	15G	15G	10G
250 - 1,000 lbs 113 - 454 kg	37G	25G	25G	15G	15G	10G	10G
1,000 - 2,000 lbs 454 - 907 kg	25G	25G	25G	15G	15G	10G	5G
2,000 - 5,000 lbs 907 - 2,268 kg	25G	25G	15G	15G	10G	10G	5G
5,000 - 10,000 lbs 2,268 - 4,536 kg	25G	15G	15G	15G	10G	10G	5G
10,000 - 15,000 lbs 4,536 - 6,804 kg	N/A	15G	15G	10G	10G	5G	5G
15,000 - 20,000 lbs 6,804 - 9,072 kg	N/A	N/A	10G	10G	5G	5G	5G
20,000 - 30,000 lbs 9,072 - 13,608 kg	N/A	N/A	N/A	5G	5G	5G	5G
30,000+ lbs 13,608+ kg	N/A	N/A	N/A	N/A	5G	5G	5G

Key Specifications	
Sensitivity Range	5G - 75G
Operating Temperature	-25°C to 80°C (-13°F to 176°F)
Duration	5 - 50 ms
Tolerance	± 15%
Status when shipped	Armable
Adhesive	Acrylic
Security	Tamper Proof, Serialized (OCR Format)
Size	1.69 x 1.69 x 0.25 in (42.93 x 42.93 x 6.35 mm)
Shelf Life	2 years when stored at standard temperature and pressure (20°C / 68° F, 1 ATM)

